

■キャブタイヤケーブル選定の目安

馬力 (HP)	容量 (kW)	定格 電流 (A)	亘長 (キャブタイヤケーブル) / キャブタイヤケーブル(スケア)													
			10	20	30	40	50	60	70	80	90	100	110	120	130	140
0.5	0.4	1.8	0.75	0.75	0.75	0.75	0.75	0.75	1.25	1.25	1.25	1.25	1.25	2.0	2.0	2.0
1	0.75	3.3	0.75	0.75	0.75	0.75	1.25	1.25	2.0	2.0	2.0	2.0	2.0	3.5	3.5	3.5
2	1.5	6.2	1.25	1.25	1.25	2.0	2.0	3.5	3.5	3.5	3.5	5.5	5.5	5.5	5.5	5.5
3	2.2	8.2	2.0	2.0	2.0	3.5	3.5	3.5	5.5	5.5	5.5	5.5	8	8	8	8
5	3.75	14.4	3.5	3.5	3.5	3.5	5.5	5.5	8	8	8	14	14	14	14	14
7.5	5.5	21.1	5.5	5.5	5.5	5.5	8	8	14	14	14	14	22	22	22	22
10	7.5	27.9	8	8	8	8	14	14	14	14	22	22	22	22	30	30
15	11	47.6	14	14	14	14	22	22	22	30	30	30	38	38	50	50
20	15	55.9	22	22	22	22	22	22	30	30	38	38	38	38	50	50
25	19	69	30	30	30	30	30	30	30	38	50	50	50	60	60	60
30	22	82	38	38	38	38	38	38	38	50	50	60	60			
50	37	137	60	60	60	60	60	60	60							