

■キャブタイヤケーブル選定の目安

馬力 (HP)	容量 (kW)	定格 電流 (A)	亘長 (キャブタイヤケーブル)／キャブタイヤケーブル(スケア)													
			10	20	30	40	50	60	70	80	90	100	110	120	130	140
0.5	0.4	1.8	0.75	0.75	0.75	0.75	0.75	0.75	1.25	1.25	1.25	1.25	1.25	2.0	2.0	2.0
1	0.75	3.3	0.75	0.75	0.75	0.75	1.25	1.25	2.0	2.0	2.0	2.0	2.0	3.5	3.5	3.5
2	1.5	6.2	1.25	1.25	1.25	2.0	2.0	3.5	3.5	3.5	3.5	5.5	5.5	5.5	5.5	5.5
3	2.2	8.2	2.0	2.0	2.0	3.5	3.5	3.5	5.5	5.5	5.5	5.5	8	8	8	8
5	3.75	14.4	3.5	3.5	3.5	3.5	5.5	5.5	8	8	8	14	14	14	14	14
7.5	5.5	21.1	5.5	5.5	5.5	5.5	8	8	14	14	14	14	22	22	22	22
10	7.5	27.9	8	8	8	8	14	14	14	14	22	22	22	22	30	30
15	11	47.6	14	14	14	14	22	22	22	30	30	30	38	38	50	50
20	15	55.9	22	22	22	22	22	22	30	30	38	38	38	38	50	50
25	19	69	30	30	30	30	30	30	30	38	50	50	50	60	60	60
30	22	82	38	38	38	38	38	38	38	50	50	60	60			
50	37	137	60	60	60	60	60	60	60							